



Specifications:  
 Current Rating:1.5A AC/DC  
 Voltage Rating:30V AC/DC  
 Contact Resistance:30m ohm. Max.  
 Insulation Resistance:1,000M ohm. min.  
 Withstanding Voltage:500V AC For One Minute  
 Operating Temperature Range:-55°C ~ +85°C  
 Material and Finish  
 Insulator:PBT (UL94V-0)  
 Contact:Phosphor Bronze  
 Plating:Gold Plated 1U”&15u”&30u”  
           Tin Plated on Solder Tail.  
 Shell:Brass,Nickel Plated 100U”  
 How To Order  
 5075AR-04-XX-XX

Blank Standard Gold Plated 1u”  
 30:Selective Gold Plated 30u”  
 15:Selective Gold Plated 15u”  
 BK:Black  
 WH:White

RoHS Compliant

REV	DATE	FILE	BY
A	05-Nov-2010		Richie
B	07-Jul-2011	ECN-CN1107004	Zhou Lin
C	11-Sep-2017	圖面更新	Jack Huang
D	23-Jul-2019	增加15U”選項	Romina Wu

DRAWN:  
Richie

CHECKED:  
Jeremy Liu

APPROVAL:  
Mike Wu

GENERAL TOLERANCE:  
 .X=±0.20  
 .XX=±0.15

UNIT: MM  
 SCALE:1:1  
 SHEET: 1 / 1  
 PROJECTION:

**Neltron Industrial Co., Ltd.**

DESCRIPTION:  
USB A Type PCB Socket Right Angle

PART NO:  
5075AR-04-XX-XX

SIZE  
**A4**