



PCB MOUNTING LAYOUT

NOTES:

1. MATERIAL:

HOUSING : NYLON 66+15%GF UL94V0 BLACK COLOR

CONTACT : (+)ELECTRODE : PHOSPHOR BRONZE 0.60MM THK
TIN PLATED OVER NICKEL

(-)ELECTRODE : BRASS 0.60MM THK
TIN PLATED OVER NICKEL

2. CURRENT RATING : 2A (AC/DC)

3. VOLTAGE RATING : 500V (AC/DC)

4. CONTACT RESISTANCE : 30 MILLIOHMS

5. INSULATION RESISTANCE : 1000 MEGAOHMS

6. TEMPERATURE RANGE : -55°C TO +105°C

7. HUMIDITY : 40°C AND 90-95% RH FOR 96 HOURS

8. RoHS COMPLIANT

3			COMF COMFORTABLE ELECTRONIC CO.LTD.		
2			NAME BATTERY HOLDER: CH075-2032LF		
1			SCALE	2:1	APPD
NO.	MODIFICATION	DATE	UNIT	MM	CHKD
			MAT'L	AS NOTES	DWN
			DATE	NOV. 15. 2010	DR NO CH075-1110
		General Tolerance Dim: 0.0 ±0.30 0.00 ±0.20 Angle: ±3° 0.000 ±0.10			