



SPECIFICATION

- (1) ITEM NO. : CH224-2032LF
- (2) HOUSING MATERIAL: PBT UL94V0, BLACK COLOR
- (3) CONTACT MATERIAL: ANODE: 0.4MM THICK BRASS TIN PLATED
CATHODE: 0.2MM THICK BRASS TIN PLATED
- (4) CURRENT RATING : 0.5A DC
- (5) VOLTAGE RATING : 12V DC
- (6) CONTACT RESISTANCE: 30 MILLIOHMS MAX
- (7) INSULATION RESISTANCE: 1000 MEGAOHMS MIN
- (8) TEMPERATURE RANGE: -55° TO +85°
- (9) HUMIDITY: 40°C±2°C , 90~95% RH FOR 96 HOURS
- (10) RoHS COMPLIANT

	1.Changed contact material from phosphor bronze to brass 2.Changed pin dimensions from 3.9 to 4.10 & 3.60		Aug/12 /2014		COMFORTABLE ELECTRONIC CO.LTD.		
	NO. MODIFICATION		DATE		NAME COIN CELL HOLDER: CH224-2032LF		
General Tolerances			The Third Angle Projection		SCALE 2:1		
0 ~ >3	± 0.10	30 ~ >120	± 0.30	UNIT MM			
3 ~ >6	± 0.10	120 ~ >400	± 0.50	MAT'L SEE SPEC.			
6 ~ >30	± 0.20	Angle: ± 3°		DATE AUG. 12. 2014			
				APPD		CHKD	
				DWN		DR NO CH224-0814	