



NOTES

1. MATERIAL:
 HOUSING: LCP+30%GF UL94V0 WHITE COLOR
 CONTACT: PHOSPHOR BRONZE 0.15 THICKNESS
 GOLD 1U" PLATED OVER Ni 50U" MIN
2. CURRENT RATING : 2A (AC/DC)
3. VOLTAGE RATING : 500V (AC/DC)
4. CONTACT RESISTANCE: 30 MILLIOHMS
5. INSULATION RESISTANCE: 500 MEGAOHMS
6. TEMPERATURE RANGE: -55°C TO +85°C
7. HUMIDITY: 40°C AND 90-95% RH FOR 96 HOURS
8. RoHS COMPLIANT

PCB MOUNTING LAYOUT

| 3 | | | COMP COMFORTABLE ELECTRONIC CO.LTD. | | |
|--------------------|-------------------------------|-------------|---|-----------|-----------------|
| 2 | | | NAME COIN CELL HOLDER: CH28-2032LF (GOLD CONTACT) | | |
| 1 | Changed contact specification | Aug/30/12 | SCALE | 2:1 | APPD 陈明 9/30/12 |
| NO. | MODIFICATION | DATE | UNIT | MM | CHKD 陈明 9/30/12 |
| General Tolerances | | | The Third Angle Projection | MAT'L | SEE NOTES |
| 0 ~ >3 | ± 0.10 | 30 ~ >120 | | ± 0.30 | DWN 陈明 9/30/12 |
| 3 ~ >6 | ± 0.10 | 120 ~ >400 | | ± 0.50 | DR NO |
| 6 ~ >30 | ± 0.20 | Angle: ± 3° | | DATE | MAY. 16. 2008 |
| | | | DR NO | CH28-0508 | |