



Recommend PCB Layout



Specifications

Current rating:1A AC,DC

Voltage rating:50V AC,DC

Temperature range:-25° to+85°

Contact resistance:20mΩ Max

Insulation resistance:100MΩ Min

Withstanding voltage:500V AC/minute

Pin Material:Phosphor Bronze/Sn-plated

Solder Tabs:Phosphor Bronze/Sn-plated

Material: LCP UL94V-0

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
A1001WR-S-02P	1.00	4.00	2.45
A1001WR-S-03P	2.00	5.00	3.45
A1001WR-S-04P	3.00	6.00	4.45
A1001WR-S-05P	4.00	7.00	5.45
A1001WR-S-06P	5.00	8.00	6.45
A1001WR-S-07P	6.00	9.00	7.45
A1001WR-S-08P	7.00	10.00	8.45
A1001WR-S-09P	8.00	11.00	9.45
A1001WR-S-10P	9.00	12.00	10.45
A1001WR-S-11P	10.00	13.00	11.45
A1001WR-S-12P	11.00	14.00	12.45
A1001WR-S-13P	12.00	15.00	13.45
A1001WR-S-14P	13.00	16.00	14.45
A1001WR-S-20P	19.00	22.00	20.45

AXXXX□□-□-NP-K-X-□□-□□-□-XXX

- 序列号
- 针座:
 - WV:直针
 - WR:弯针
- S: SMT
- F: 带柱
- SF: SMT带柱
- E: 带扣
- 塑胶材质:
 - 0:PA66-V0
 - 1:LCP
 - 2:PA66-V2
 - 3:PBT
 - 4:PA46
 - 5:PPO
 - 6:PA6T
 - 9:PA9T
- 材质电镀:
 - BS:黄铜镀锡
 - BG:黄铜镀金
 - PS:磷铜镀锡
 - PG:磷铜镀金
 - G1:镀金1U
 - G3:镀金3U
 - G5:镀金5U
- 颜色:
 - WE:白
 - BK:黑
 - RY:米黄
 - RD:红
 - BN:棕
 - GY:灰
 - BE:蓝
 - NA:透明
- 包装方式:
 - P:袋装
 - T:管装
 - D:盒装
 - R:卷装

Unit mm



协威亚洲有限公司
HERWELL ASIA LTD

			DRAWN BY 李权 2017.09.02	APPROVED BY 黄维 2017.09.02	TITLE: SM04B-SRSS-TB Compatible
			GENERAL TOLERANCE		DRAW NO: DG01032-0060-01
			.X ±0.25	ANGLE ±	
AO	NEW RELEASE	2017.09.02	.XX ±0.15		
REV.	DESCRIPTION	DATE	.XXX ±0.05		