


# EPC1012 – Enhancement Mode Power Transistor

 $V_{DSS}, 200\text{ V}$ 
 $R_{DS(ON)}, 100\text{ m}\Omega$ 
 $I_D, 3\text{ A}$ 


Gallium Nitride is grown on Silicon Wafers and processed using standard CMOS equipment leveraging the infrastructure that has been developed over the last 55 years. GaN's exceptionally high electron mobility and low temperature coefficient allows very low  $R_{DS(ON)}$ , while its lateral device structure and majority carrier diode provide exceptionally low  $Q_G$  and zero  $Q_{RR}$ . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.



EPC Power Transistors are supplied only in passivated die form with solder bumps

### Applications

- High Speed DC-DC conversion
- Class D Audio
- Hard Switched and High Frequency Circuits

### Benefits

- Ultra High Efficiency
- Ultra Low  $R_{DS(on)}$
- Ultra low  $Q_G$
- Ultra small footprint

Maximum Ratings			
$V_{DS}$	Drain-to-Source Voltage	200	V
$I_D$	Continuous ( $T_A = 25^\circ\text{C}, \theta_{JA} = 100$ )	3	A
	Pulsed ( $25^\circ\text{C}, T_{\text{pulse}} = 300\ \mu\text{s}$ )	12	
$V_{GS}$	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-5	
$T_J$	Operating Temperature	-40 to 125	$^\circ\text{C}$
$T_{STG}$	Storage Temperature	-40 to 150	

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
<b>Static Characteristics</b> ( $T_J = 25^\circ\text{C}$ unless otherwise stated)					
$BV_{DSS}$	Drain-to-Source Voltage	$V_{GS} = 0\text{ V}, I_D = 50\ \mu\text{A}$	200		V
$I_{DSS}$	Drain Source Leakage	$V_{DS} = 160\text{ V}, V_{GS} = 0\text{ V}$	10	40	$\mu\text{A}$
$I_{GSS}$	Gate-Source Forward Leakage	$V_{GS} = 5\text{ V}$	0.2	1	mA
	Gate-Source Reverse Leakage	$V_{GS} = -5\text{ V}$	0.1	0.5	
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 1\text{ mA}$	0.7	1.4	V
$R_{DS(ON)}$	Drain-Source On Resistance	$V_{GS} = 5\text{ V}, I_D = 5\text{ A}$	70	100	$\text{m}\Omega$
<b>Dynamic Characteristics</b> ( $T_J = 25^\circ\text{C}$ unless otherwise stated)					
$C_{ISS}$	Input Capacitance	$V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$	110		pF
$C_{OSS}$	Output Capacitance		80		
$C_{RSS}$	Reverse Transfer Capacitance		7.5		
$Q_G$	Total Gate Charge ( $V_{GS} = 5\text{ V}$ )	$V_{DS} = 100\text{ V}, I_D = 3\text{ A}$	1.9		nC
$Q_{GD}$	Gate to Drain Charge		0.9		
$Q_{GS}$	Gate to Source Charge		0.37		
$Q_{OSS}$	Output Charge		10		
$Q_{RR}$	Source-Drain Recovery Charge		0		
<b>Source-Drain Characteristics</b> ( $T_J = 25^\circ\text{C}$ unless otherwise stated)					
$V_{SD}$	Source-Drain Forward Voltage	$I_S = 0.5\text{ A}, V_{GS} = 0\text{ V}, T = 25^\circ\text{C}$	1.8		V
		$I_S = 0.5\text{ A}, V_{GS} = 0\text{ V}, T = 125^\circ\text{C}$	1.75		

Figure 1: Typical Output Characteristics




Figure 2: Transfer Characteristics




Figure 3:  $R_{DS(ON)}$  vs  $V_G$  for Various Current




Figure 4:  $R_{DS(ON)}$  vs  $V_G$  for Various Temperature




Figure 5: Capacitance




Figure 6: Gate Charge




Figure 7: Reverse Drain-Source Characteristics




Figure 8: Normalized On Resistance Vs Temperature




Figure 9: Normalized Threshold Voltage






Figure 10: Gate Current



TAPE AND REEL CONFIGURATION


4mm pitch, 8mm wide tape on 7" reel



Dimension (mm)	EPC1012		
	target	min	max
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (see note)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (see note)	2.00	1.95	2.05
g	1.5	1.5	1.6

Note: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole


**DIE MARKINGS**



Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking line 2	Lot_Date Code Marking Line 3
EPC1012	1012	YYYY	ZZZZ


**DIE OUTLINE**

Bottom View




DIM	MICROMETERS		
	MIN	Nominal	MAX
A	1681	1711	1741
B	889	919	949
c	666	669	672
d	252	255	258
e	230	245	260
f	297	300	303
g	600	600	600

Side View



**RECOMMENDED LAND PATTERN**

(measurements in  $\mu\text{m}$ )



Pad no. 1 is Gate;  
Pads no. 3 is Drain;  
Pads no. 2 and 4 are Source.