



■ SPECIFICATIONS

- Voltage Rating : 150V AC/DC
- Current Rating : 1A AC/DC
- Withstanding Voltage : 1,000V AC /minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 40°C to + 105°C
- Contact Resistance : 10mΩ max

■ SIP SOCKET

- Part No. :
- Poles : 2-40(Single Row)
- Material : Beu : Beryllium Copper , Gold Plated
Sleeve Barrel : Brass , Tin Plated
Base : PPS UL94V-0

Poles	Part No.	Dimensions(mm)		Poles	Part No.	Dimensions(mm)	
		A	B			A	B
2		2.54	5.08	22		53.34	55.88
3		5.08	7.62	23		55.88	58.42
4		7.62	10.16	24		58.42	60.96
5		10.16	12.70	25		60.96	63.50
6		12.70	15.24	26		63.50	66.04
7		15.24	17.78	27		66.04	68.58
8		17.78	20.32	28		68.58	71.12
9		20.32	22.86	29		71.12	73.66
10		22.86	25.40	30		73.66	76.20
11		25.40	27.94	31		76.20	78.74
12		27.94	30.48	32		78.74	81.28
13		30.48	33.02	33		81.28	83.82
14		33.02	35.56	34		83.82	86.36
15		35.56	38.10	35		86.36	88.90
16		38.10	40.64	36		88.90	91.44
17		40.64	43.18	37		91.44	93.98
18		43.18	45.72	38		93.98	96.52
19		45.72	48.26	39		96.52	99.06
20		48.26	50.80	40		99.06	101.6
21		50.80	53.34				

PART NO	APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
				.0	±0.3						
2.54mm SIP Socket(Single Row)	CHECKED BY	PROJ	VER NO.	.00	±0.2	ECR	RoHS Compliant	06/04/01			
				.000	±0.1		200812-010	08/12/10			
	DRAWN BY	DATE	SIZE	ANGLE					CUSTOMER		
		2008/12/10	A4	0°	±				Conforms to The RoHS Instruction		
				.0°	±						