


仕様
SPECIFICATION

1. 定格: MJ-095N=DC3.15V 2A (電圧区分1 JSAJ1)
RATING MJ-096N=DC6.3V 2A (電圧区分2 JSAJ2)
MJ-097N=DC10.5V 2A (電圧区分3 JSAJ3)
2. 絶縁抵抗: DC500V/100M 以上。
INSULATION RESISTANCE:
DC500V/100M MIN.
3. 耐電圧: AC500V 1分間。
WITHSTAND VOLTAGE:
AC500V 1MINUTE.
4. 接触抵抗: 30m 以下
CONTACT RESISTANCE:
30m MAX

回路
CIRCUIT



品番 MODEL No.	A部	B部	適合プラグ MATE PLUG
MJ-095N	0.65	2.5	2.35 X 0.7
MJ-096N	1.65	4.2	4.0 X 1.7
MJ-097N	1.65	4.9	4.75 X 1.7

LET	PART NAME	MATERIAL	QTY	FINISH	NOTE	TOLERANCE	SCALE	DATE	DESING	DRAW	INSPE	APRO
7	接触パネ CONTACT	PBS-EH t=0.25	1	Ni		±0.3	2/1	10/4/6	M.K	N.I		
6	キャップ CAP	PE	1									
5	プラグ B TERMINAL B	BSR t=0.3	1	Ni		MODEL		QTY	PART NAME	DCプラグインラインジャック DC INLINE JACK		
4	プラグ A TERMINAL A	BSR t=0.3	1	Ni		型式			品名	No. MJ-095N, 096N, 097N		
3	ピン PIN	BSBM	1	Ni		MATERIAL				DRAW.NO	MJ096N	
2	リンク METAL	BSBM	1	Ni		材質				図番		
1	ボディ BODY	PA	1			FINISH						
						処理			MARUSHIN ELECTRIC MFG. CO., LTD.			