



仕様
SPECIFICATION

1. 定格: DC12V 1A
RATING
2. 接触抵抗: 30m 以下。
CONTACT RESISTANCE:
30m MAX.
3. 絶縁抵抗: DC500V/100M 以上。
INSULATION RESISTANCE:
DC500V/100M MIN.
4. 耐電圧: AC500V 1分間。
WITHSTAND VOLTAGE:
AC500V 1MINUTE.

取付穴参考寸法
MOUNTING HOLE DIMENSION
(t=1.0~1.8mm)

A	
MJ60	1.95
MJ61	2.35

TOLERANCE	SCALE	DATE	DESING	DRAW	INSPE	APRO
±0.3	2/1	01/1/24	M.K	N.1		
MODEL 型式	QTY		PART NAME 品名	スナップインDCジャック SNAP-IN MOUNTING DC JACK No.MJ60/MJ61		
MATERIAL 材質				DRAW.NO 図番	MJ60	
FINISH 処理	MARUSHIN ELECTRIC MFG.CO.,LTD.					

LET	PART NAME	MATERIAL	QTY	FINISH	NOTE
4	TERMINAL センター端子	BSR t=0.3	1	Ni	
3	CONTACT SPRING 可動端子	PBS t=0.3	1	Ni	
2	PIN センターピン	BSW	1	Ni	
1	BODY 本体	PA	1		