






# 訂單圖

版次	修改日期	敘	述



規格說明: Specifications:  
 电气特性: Electrical:  
 1. 额定电流: Current Rating  
 1.5A/contact terminal  
 2. 额定电压: Voltage Rating  
 30V DC  
 3. 接触电阻: Contact Resistance  
 30 milliohms MAX  
 4. 绝缘电压: Dielectric Withstanding Voltage:  
 500 V AC AT Sea Level  
 5. 绝缘电阻: Insulation Resistance:  
 1000MEGA ohms MIN

物理性能: Mechanical:  
 1. 插拔力: Connector Mate and Unmate Force  
 Mate force: 3.57kgf(MAX)  
 Unmate force: 1.02kgf(MIN)

原材料: Material:  
 1. 塑胶: Housing:  
 High Temperature Thermoplastics,

2. 端子: Contact: Copper Alloy C1591  
 3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:  
 1. 端子: Contact: Plated Gold in Mating Area  
 Tin On Solder Tails

端子四周镀50U"(MIN)锡,镀金区域镀100-200U"镀金1U"

2. 外壳: Shell:  
 铜壳四周镀80U"(MIN)锡

1		長交編號	AR06-MRUSB-2B-D14NI-S306	長交數量	PCS	
2		客戶編號	MRUSB-2B-D14NI-S306	長交淨重	KGS	
3		UNIT: MM	麥頭: ENN	長交毛重	KGS	PART NAME: Micro Usb B Type 5P Female Dip
4		TOLERANCE UNSPECIFIEDE		廠商數量	PCS	
5		X ±0.5	XXX ±30	廠商淨重	KGS	外箱編號 MRUSB-2B-D14NI-S306 製圖日期 2019.10.01
6		X ±1.0	XXXX ±200	廠商毛重	KGS	
		XX ±5.0	XXXXX ±1000	廠商毛重	KGS	外箱紙箱 38*32*26CM 廠商紙箱 38*32*26CM