

# SPECIFICATION

CCD: SONY ICX642AKA-A

MODEL NO.	MTV-34KK0N	MTV-34KK0P
TV SYSTEM	NTSC	PAL
IMAGE SENSOR	1/4-inch CCD Image Sensor	
CCD TOTAL PIXELS	542 (H) x 496 (V)	542 (H) x 586(V)
SCANNING SYSTEM	525 lines, 60 fields/sec	625 lines, 50 fields/sec
SYNC SYSTEM	Internal	
MINIMUM ILLUMINATION	0.8 Lux F1.2 5600°K	
LENS & VIEW ANGLE	3.6 mm F2.0 / 68° (Option 2.2,2.5,3.0,4.0,6.0,8.0,12.0 mm)	
RESOLUTION	380 TVL / 470 TVL(Enhance)	
S/N RATIO	52dB (MIN) / 60dB (TYP) (AGC OFF)	
WHITE BALANCE	Auto high speed White Balance ATW / FIX / AWC	
WHITE BALANCE RANGE	3200---12000 °K	
AUTO IRIS	A.E.S.	
ELECTRONIC SHUTTER	1/60~1/120,000 sec.	1/50~1/120,000 sec.
VIDEO OUTPUT	1.0V p-p composite video at 75 ohm	
GAMMA CORRECTION	0.45	
MIRROR FUNCTION	ON / OFF Switch	
2X ZOOM FUNCTION	ON / OFF Switch	
GAIN CONTROL	AGC	
OPERATION TEMPERATURE	-20°C TO 50°C	
OPERATIONAL HUMIDITY	within 85% RH	
POWER SUPPLY	DC12V / 80mA	

\*The specifications and appearance of the product may changed without notice.

Dimension: Unit (mm) ±0.5mm

MTV-34KON後継品

