SUPERTECH ELECTRONIC CO., LTD.

DISC CERAMIC CAPACITOR

Part No. : RDDS330K1H5L1

MECHANICAL :

Thickness (T) : 3.5 mm Max.

Lead Diameter : 0.52 mm ± 0.05 mm

Soldering Test : 260 ℃ ± 5 ℃

Pulling Test : 2 KG

Marking : 33K

CP Wire



External Dimensions (D)	5mm ± 1mm
Lead Spacing (F)	5mm ± 0.8mm
Thickness (T)	3.5mm Max.
Lead Length (L)	25mm ± 3mm
Lead Diameter (d)	0.52mm ± 0.05mm
Lead Coating (G)	1.5mm Max.

ELECTRICAL :

Capacitance : 33PF

Capacitance Tolerance : + - 10 %

Q or ~~DF~~ : CAP.≧30PF;Q≧1000

: CAP.<30PF;Q≧400+20C

Insulation Resistance : ≧ 10000MΩ

Working Voltage : 50 V DC

Dielectric Withstanding : 150 V DC for 1～5 sec

Temperature Characteristic :

According to EIA SL The Capacitance change of +350 ～ -1000 PPM/℃

between the temperature range of - 25 ℃ ~ + 85 ℃

TESTING INSTRUMENTS :

1 . TEMPERATURE COMPENSATING TYPE : HP4278A

2 . HIGH DIELECTRIC TYPE : HP4265A

TESTING CONDITIONS :

Testing Frequency : 1MHz

Testing Voltage : 1.0Vrms

＊Remarks: Withstand voltage below 100VDc, all need to comply with the manufacturing specifications of Coating's non-leakable silver electrode

DATE : 2021/5/14

APPROVER : Sally Hsu