

<i>Data approve</i>	Product	Solid State Module	No	FT-SA-210407	Ver.	A0
	Series	SSR Series	Date	2021/04/26		
Model	型號	SSR-10DA				
Rated current	額定電流	10A max.				
Surge current	耐突波電流	135A				
I²t for fuse	熔斷電流	144A ² S				
Peak voltage	耐突波電壓	1200 VAC min.				
Output voltage	輸出電壓	24 ~ 380 VAC				
General specification / 共同規格						
Input method	輸入方式	4 ~ 32 VDC				
Turn off voltage	關閉電源	< 3.5 VDC				
Input current	輸入電流	12mA max.				
Leakage current	洩漏電流	5 mA max.				
Response time	反應時間	8.3ms max.(60Hz)				
Input immunity	輸入耐突波	2KV (EN61000-4-4)				
Isolation strength	電介強度	4KVrms (EN60950/VDE0805)				
Insulation strength	絕緣強度	100MΩ / 500VDC (EN60950/VDE0805)				
Housing material	外殼材質	防火 ABS (UL:94V0)				
Screw of Size	螺絲尺寸	M4				
Circumstance	工作環境	- 40 °C ~ + 80 °C ; 35~85%RH				
Connection / 接線圖				Outline dimension / 外型尺寸圖		
發行章				品管部		