


NOTES:

1. NOMINAL IMPEDANCE 50 OHMS.
2. FREQUENCY RANGE: 0-4 GHz.
3. MAX PEAK VOLTAGE: 500V.
4. INSULATION RESISTANCE: 5000 MEGOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VOLTS RMS.

NO	Description	Material	Finish	Dimensions Are In Millimeters Unless Otherwise Specified Tolerances		 COSMTEC RESOURCES CO., LTD											
1	Post	Brass	Tin	0.5-6 = ± 0.2 6-30 = ± 0.4 30-120 = ± 0.6 120-315 = ± 1.0 315-1000 = ± 1.6 1000-2000 = ± 2.4	DRAFT CHECKED APPROVED	Part No 圖號 Title 圖名 Date 日期	B-057-HP					Scale 比例		Unit 單位		Rev 版次	
	Housing	PBT+30%G.F.	White														
	Body	Zinc Alloy	Nickel				AUG/09/2010					2:1		m/m		A	
	Insulator	P.P.	-														
	Grounding	Cu Covered Steel	Tin														
	Contact	P.H Bronze	Gold+Tin														
2	Lock Washer	SK-5	Nickel														
3	Nut	Brass	Nickel														