

# BCR30FM-8LB

400V - 30A - Triac  
Medium Power Use


R07DS0965EJ0001  
Rev.0.01  
Nov 28, 2012

## Features

- $I_{T(\text{RMS})}$  : 30 A
- $V_{\text{DRM}}$  : 400 V
- $T_j$ : 150 °C
- $I_{\text{FGTI}}, I_{\text{RGTI}}, I_{\text{RGTHI}}$  : 30 mA
- Insulated Type
- Planar Passivation Type
- $V_{\text{iso}}$ : 2000 V

## Outline

RENESAS Package code: PRSS0003AG-A  
(Package name: TO-220FP)



- $T_1$  Terminal
- $T_2$  Terminal
- Gate Terminal

## Applications

Contactless AC switch, electric heater control, light dimmer, on/off and speed control of small induction motor, on/off control of copier lamp

## Maximum Ratings

Parameter	Symbol	Voltage class		Unit
		8		
Repetitive peak off-state voltage <sup>Note1</sup>	$V_{\text{DRM}}$	400		V
Non-repetitive peak off-state voltage <sup>Note1</sup>	$V_{\text{DSM}}$	500		V

Parameter	Symbol	Ratings	Unit	Conditions
RMS on-state current	$I_{T(\text{RMS})}$	30	A	Commercial frequency, sine full wave 360° conduction, $T_c = 33^\circ\text{C}$
Surge on-state current	$I_{\text{TSM}}$	300	A	50 Hz sinewave 1 full cycle, peak value, non-repetitive
$I^2t$ for fusion	$I^2t$	450	$\text{A}^2\text{s}$	Value corresponding to 1 cycle of half wave 50 Hz, surge on-state current
Peak gate power dissipation	$P_{\text{GM}}$	5	W	
Average gate power dissipation	$P_{\text{G(AV)}}$	0.5	W	
Peak gate voltage	$V_{\text{GM}}$	10	V	
Peak gate current	$I_{\text{GM}}$	2	A	
Junction Temperature	$T_j$	-40 to +150	$^\circ\text{C}$	
Storage temperature	$T_{\text{stg}}$	-40 to +150	$^\circ\text{C}$	
Mass	—	1.9	g	Typical value
Isolation voltage <sup>Note5</sup>	$V_{\text{iso}}$	2000	V	$T_a = 25^\circ\text{C}$ , AC 1 minute, $T_1 \bullet T_2 \bullet G$ terminal to case

## Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
Repetitive peak off-state current	$I_{DRM}$	—	—	3.0	mA	$T_j = 125^\circ C, V_{DRM}$ applied
		—	—	5.0	mA	$T_j = 150^\circ C, V_{DRM}$ applied
On-state voltage	$V_{TM}$	—	—	1.5	V	$T_c = 25^\circ C, I_{TM} = 45 A$ , instantaneous measurement
Gate trigger voltage <sup>Note2</sup>	I	$V_{FGT_I}$	—	2.0	V	$T_j = 25^\circ C, V_D = 6 V, R_L = 6 \Omega, R_G = 330 \Omega$
	II	$V_{RGTI}$	—	2.0	V	
	III	$V_{RGTI_{III}}$	—	2.0	V	
Gate trigger current <sup>Note2</sup>	I	$I_{FGT_I}$	—	30	mA	$T_j = 25^\circ C, V_D = 6 V, R_L = 6 \Omega, R_G = 330 \Omega$
	II	$I_{RGTI}$	—	30	mA	
	III	$I_{RGTI_{III}}$	—	30	mA	
Gate non-trigger voltage	$V_{GD}$	0.2	—	—	V	$T_j = 125^\circ C, V_D = 1/2 V_{DRM}$
		0.1	—	—	V	$T_j = 150^\circ C, V_D = 1/2 V_{DRM}$
Thermal resistance	$R_{th(j-c)}$	—	—	3.0	°C/W	Junction to case <sup>Note3</sup>
Critical-rate of rise of off-state commutation voltage <sup>Note4</sup>	$(dv/dt)c$	10	—	—	V/μs	$T_j = 125^\circ C$
		1	—	—	V/μs	$T_j = 150^\circ C$

Notes: 1. Gate open.

2. Measurement using the gate trigger characteristics measurement circuit.
3. The contact thermal resistance  $R_{th(c-f)}$  in case of greasing is  $0.5^\circ C/W$ .
4. Test conditions of the critical-rate of rise of off-state commutation voltage is shown in the table below.
5. Make sure that your finished product containing this device meets your safe isolation requirements.  
For safety, it's advisable that heatsink is electrically floating.

Test conditions	Commutating voltage and current waveforms (inductive load)
1. Junction temperature $T_j = 125^\circ C/150^\circ C$ 2. Rate of decay of on-state commuting current $(di/dt)c = -16 A/ms$ 3. Peak off-state voltage $V_D = 400 V$	<p>The diagram illustrates the waveforms for commutation in an inductive load. It shows three plots sharing a common time axis:</p> <ul style="list-style-type: none"> <li><b>Supply Voltage:</b> A sinusoidal wave starting at zero and reaching a peak.</li> <li><b>Main Current:</b> A curve that starts at a positive value, decreases linearly (labeled <math>(di/dt)c</math>), and then drops sharply to zero.</li> <li><b>Main Voltage:</b> A curve that starts at zero, increases linearly (labeled <math>(dv/dt)c</math>), and then remains constant at the peak value <math>V_D</math>.</li> </ul>

## Package Dimensions

Package Name	JEITA Package Code	RENESAS Code	Previous Code	MASS[Typ.]	Unit: mm
TO-220FP	—	PRSS0003AG-A	—	1.9g	

## Ordering Information

Orderable Part Number	Packing	Quantity	Remark
BCR30FM-8LB#BB0	Tube	50 pcs.	Straight type
BCR30FM-8LB-A8#BB0	Tube	50 pcs.	A8 Lead form

Note: Please confirm the specification about the shipping in detail.