


Applications:

High Speed Modems

CIMs

Hybrid Fiber Coax(HFC Networks)

CATV

Features/Benefits:

Patent pending contact design

Provides a truly cylindrical coaxial contact 30dB return loss to 1GHz

Multiple PCB mount packages:

SMD, edge mount, right angle and straight Accommodate.022-042in. center conductor sizes

Specifications:

Impedance: 75Ω

RF Leakage: -100dB min.@1GHz

Temperature Range: -45°C~+85°C

Note:

1. Body: Brass per JIS-C3604

2. Connector Interface PER MIL-STD-348A

3.Part to be clean and free burrs

4. Nickel PL 70U" thick over copper strike

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Delrin	-
3	Contact	Brass	Tin
4	Washer	Steel	Nickel
5	Nut	Brass	Nickel

**Dimensions Are In Millimeters
Unless Otherwise Specified Tolerances**

0.5-6 =	± 0.2
6-30 =	± 0.4
30-120 =	± 0.6
120-315 =	± 1.0
315-1000 =	± 1.6
1000-2000 =	± 2.4

DRAFT
CHECKED
APPROVED

COSMTEC RESOURCES CO., LTD
Part No
圖號
F-012
Title
圖名
F JACK SOLDER BULKHEAD W/NUT+WASHER
Date
日期
MAR/01/2013
比例
Scale
單位
Unit
m/m
版次
Rev
A