



NOTE:

RATING - 12 VDC 15 A
 DIELECTRIC STRENGTH - 500 VAC FOR
 ONE MINUTE
 INSULATION RESISTANCE - 100 MEGA OHM
 min. FOR 1 MINU
 -TE

9	FASTON TERMINAL	BRASS	1	CHROMATE-P	t=0.8										
8	CENTER TERMINAL	BRASS	1	Ni-P											
7	WASHER	STEEL	1	UNI-CHRO-P											
6	INSULATOR B	PHOENOL	1			TOLERANCE	SCALE	DATE	DESING	DRAW	INSPE	AFRO			
5	CENTER BAR	BRASS	1	Ni-P		±0.3	1/1			N.1					
4	INSULATOR A	CERAMIC	1			MODEL		QTY	PART NAME	シカーソケット					
3	CONTACT SPRING	STEEL	1	Ni-P		型式			品名	MYBC-012S					
2	HOUSING B	STEEL	1	CHROMATE-P		MATERIAL				DRAW.NO		MYBC-012S			
1	HOUSING A		1	CHROME -P		材質				図番					
LET	PART NAME	MATERIAL	QTY	FINISH	NOTE	FINISH									
						処理									

EST MARUSHI ELECTRIC MFG. CO., LTD.