



## NRJ6HH-AU

スリムジャックは水平基板取り付けタイプのフォーンジャックです。

取り付け用のナットは別売りで、用途に合わせてお選び頂けます。

### Features & Benefits

スリムフォーンジャック

- ・3極、3スイッチ (S/SN/R/RN/T/TN) ステレオ仕様
- ・コンタクト：金メッキ
- ・ノーズ：プラスチック製ハーフスレッド

## Technical Information

Product	
<b>Title</b>	NRJ6HH-AU
<b>Connection Type</b>	Jack
<b>Gender</b>	female

Electrical	
<b>Contact resistance</b>	< 10 mΩ
<b>Contact resistance</b>	< 10 mΩ
<b>Dielectric strength</b>	1 kVdc
<b>Insulation resistance</b>	≥ 1 GΩ @ 500 V dc
<b>Rated current per contact</b>	3 A
<b>Rated current per contact</b>	0,50 A @ 50 V (Switch contact)
<b>Switching contacts</b>	3

Mechanical	
<b>Insertion force</b>	< 30 N
<b>Withdrawal force</b>	> 10 N
<b>Lifetime</b>	> 10000 mating cycles
<b>Panel thickness</b>	< 1 mm
<b>Wiresize</b>	
<b>Wiring</b>	Horizontal PCB mount
<b>Locking device</b>	Retention spring
<b>Mounting direction</b>	Rear mounting
<b>Chassis shape</b>	11.2 mm

Material	
Cap / Nut / Washer	PA 6.6 15% GR
Contact plating	0.2 µm Au
Contacts	Bronze (CuSn6)
Shell	Polyamide (PA 6.6 30 % GR) UL 94 V0
Ring Nut	Brass (Ni plated)

Environmental	
Standard compliance	EIA RS 453, IEC 60603-11
Solderability	Complies with IEC 60068-2-20
Temperature range	-25 °C to +70 °C