



PCB LAYOUT

ELECTRICAL CHARACTERISTICS

1. RATING: DC 30V 0.1A
2. CONTACT RESISTANCE: 100mΩ MAX
3. INSULATION RESISTANCE: 100MΩ MIN
4. DIELECTRIC STRENGTH: AC 250V(50~60Hz)/60S

MECHANICAL CHARACTERISTICS

1. PRACTICAL TEMPERATURE RANG: -40℃~+85℃
2. OPERATING FORCE: 180±50gf
3. MECHANICAL LIFE: 30,000 cycles

8	SPRING	STEEL STRIP	1	NI PLATED OR NATURAL	TOLERANCE UNLESS SPECIFIED					
7	STEEL HOOK	STAINLESS STEEL	1	NATURAL						
6	CONTACT(CLIP)	BRONZE	2	AG COVERED	WITHIN 1.5mm : ±0.1mm	A	25-Oct-2009			
5	CASE	PBT	1	BLACK	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.	
4	TERMAINAL	BRASS STRIP	6	AG PLATED	TITLE : PUSH SWITCH			UNIT : mm	DRWG NO.: PB22E70-00	
3	TERMAINALBASE	PBT	1	BLACK	MODEL:PB-22E70L(Non-Directional type)			SCALE: 5:1	DWN.	
2	COVER	POM	1	WHITE	XIAMEN JINBEILI ELECTRONICS CO.,LTD			CHK'D		
1	KNOB	POM	1	BLUE				APPD.		
NO.	PARTS	MATERIALS	Q'TY	FINISH						