



**SPECIFICATIONS**

- 1、Current Rating: 2A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance:  $20\text{m}\Omega$  Max
- 5、Insulation Resistance:  $1000\text{M}\Omega$  Min
- 6、Withstanding Voltang:  $1000\text{V AC/minute}$
- 7、Material: Wafer LCP, UL94V-0  
PIN Brass Tin-plated  
Solder tad Brass Tin-plated

| 编 号         | 尺寸 (mm) |       |
|-------------|---------|-------|
|             | A       | B     |
| A2006WF-02A | 2.00    | 8.00  |
| A2006WF-03A | 4.00    | 10.00 |
| A2006WF-04A | 6.00    | 12.00 |
| A2006WF-05A | 8.00    | 14.00 |
| A2006WF-06A | 10.00   | 16.00 |
| A2006WF-07A | 12.00   | 18.00 |
| A2006WF-08A | 14.00   | 20.00 |
| A2006WF-09A | 16.00   | 22.00 |
| A2006WF-10A | 18.00   | 24.00 |
| A2006WF-11A | 20.00   | 26.00 |
| A2006WF-12A | 22.00   | 28.00 |
| A2006WF-20A | 38.00   | 44.00 |