



PCB MOUNTING LAYOUT



SPECIFICATION

- (1) ITEM NO. : CH030-2430LF
- (2) HOUSING MATERIAL: PBT UL94V0, BLACK COLOR
- (3) CONTACT MATERIAL: 0.5MM THICK SPRING STEEL NICKEL PLATED
- (4) CURRENT RATING : 0.5A (AC/DC)
- (5) VOLTAGE RATING : 500V (AC/DC)
- (6) CONTACT RESISTANCE: 30 MILLIOHMS
- (7) INSULATION RESISTANCE: 1000 MEGAOHMS
- (8) TEMPERATURE RANGE: -55° C TO +85° C
- (9) HUMIDITY: 40° C AND 90-95% RH FOR 96 HOURS
- (10) RoHS COMPLIANT

SECTION A-A

3			COMFORTABLE ELECTRONIC CO.LTD.		
2					
1			NAME	COIN CELL HOLDER: CH030-2430LF	
NO.	MODIFICATION	DATE	SCALE	2:1	APPD
General Tolerances			UNIT	MM	CHKD
0 ~ >3	± 0.10	30 ~ >120 ± 0.30	 The Third Angle Projection	MAT'L	SEE SPEC.
3 ~ >6	± 0.10	120 ~ >400 ± 0.50		DATE	NOV. 18. 2013
6 ~ >30	± 0.20	Angle: ± 3°		DWN	DR NO
					CH030-1113