


2.54 ± 0.05

Pin 0.50x0.25

2.54 ± 0.10



Pc Board Layout

Material :

Insulator : 30% Glass Fiber PBT, UL 94V-0
 Contact : Phosphor Bronze, Gold flash plating

Specification :

Current : 3 Amp
 Insulation Resistance : 5,000 Mohm min. at DC 500V
 Contact resistance : 20 mOhm max. at DC 100mA
 Dielectric Voltage : AC 500V for 1 minute
 Operation temperature : - 40°C ~ + 105°C

Dimensions :

P/N	Poles	Dim. A	Dim. B
C-02482	2x5	10.16	13.20
C-02484	2x7	15.24	18.28
C-02485	2x20	48.26	51.30
C-02486	2x25	60.96	64.00

- * Poles available 2x2 ~ 2x40 pins
- * Pin changable for required lengths

E				Drawn	General Tolerance			Akizuki Denshi Tsusho Co., Ltd.		
D					.0	.00	.000			
C				Checked	± 0.15	± 0.10	± 0.05	Title : 2.54mm Female Header, Dual row, Straight Dip type Insulator Height 8.5mm, Contacts 10.0mm (Dip PCB)		
B					Unit : mm					
A				Appraisal	Scale :			Part No.	Ref. Demensions table	File No. : UIC-FH-2X00SG(10)
Rev.	Date	File	BY		Sheet : 1 / 1					