



SECTION A-A

**Material**

Insulator: PBT UL 94V-0  
 Contact: Brass  
 Contact plating: Gold over Nickel

**Specification**

Current Rating: 1 Amp.  
 Insulation Resistance: 1,000 MΩ min.  
 Contact Resistance: 20 mΩ max.  
 Withstanding Voltage: 500V AC for 1 minute  
 Operation temperature: - 40°C ~ + 105°C  
 Max Processing Temp.: 200°C for 10 seconds  
 Insertion Force: 0.4 ± 0.2 kgf  
 Withdraw Force: 0.2 ± 0.1 kgf

**Order Information**

**MJ127 - 3 C - X**

- \* Insulator color:
  - Balnk - Black
  - R - Red
  - W - White
  - G - Green
  - U - Blue
  - Y - Yellow
- \* C - Closed cover
- \* O - Opened cover
- \* Insulator Height - 3.0mm

E				Drawn:	General Tolerance		
D				Jack Lin	.0	.00	.000
C	16-Dec-16	Change width	Jack	Checked:	±0.30	±0.20	
B	4-Jan-13	change Logo	David	Ivy Lee	Unit : mm		
A	28-Nov-07	new release	Jack	Appraisal:	Scale :		
Rev.	Date	File	BY	Simon Chen	Sheet : 1/1		



**Useconn**  
*Electronics Ltd.*

Part No.	<b>MJ127-3C-X</b>
File No.	RMMJ127-3C-X-Rev C

Title: 1.27mm Mini Jumper  
 3mm Height, Closed Cover type