



ELECTRICAL CHARACTERISTICS

- 1. RATING: DC 30V 0.1A
- 2. CONTACT RESISTANCE: 100mΩ MAX
- 3. INSULATION RESISTANCE: 100MΩ MIN
- 4. DIELECTRIC STRENGTH: AC 250V (50~60Hz)/60S

MECHANICAL CHARACTERISTICS

- 1. PRACTICAL TEMPERATURE RANG: -25°C~+70°C
- 2. OPERATING FORCE: 230±50gf
- 3. MECHANICAL LIFE: 10,000 cycles

**P.C.B LAYOUT
TOP VIEW**

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
8									
7	CONTACT	BRONZE	2	Ag PLATED					
6	CAM STICK	STEEL WIRE	1	NATURAL	WITHIN 1.5mm: ±0.1mm	A	25-Jun-2011		
5	TERMINAL	BRASS	6	Ag PLATED	OVER 1.5mm: ±0.2mm				
4	SPRING	STEEL WIRE	1	NATURAL					
3	COVER	PBT	1	BLACK	TITLE : PUSH SWITCH		UNIT : mm	DRWG NO.:	
2	BUTTON	POM	1	WHITE/BLACK	MODEL: PB-22E85L		SCALE: 5:1	DWN.	
1	CASE	PBT	1	BLACK	XIAMEN JINBEILI ELECTRONICS CO.,LTD			CHK'D	
									APPD.